

# EVO1000S



# A New Standard of Innovation and Quality

The EVO1000S is a display of pure craftsmanship and ingenuity, with a strong load capacity of 1000kg packed in a nice, clean Scandinavian design. What really separates our product from the competitors is the self-designed construction, which allows for low installation costs, highest possible flexibility and much more.

- ◆ 55 different platform sizes to choose from and a shaft pit of only 110mm means we can always offer you a lift that fits exactly to your building.
- ◆ Every EVO1000S comes with a full height platform back in a modern design, which also provides you with correct lighting during your ride.
- ◆ A fantastic design and construction for an easy and quick installation of only 2-4 days! Plug n' play all the way through.
- ◆ Competitive material prices together with the low installation costs make the EVO1000S one of the best priced lifts on the market.

Thanks to our great design, our strong construction and our flexibility, EVO1000S fits into all environments, both public and industrial. Hospitals, care homes, arenas, schools, offices, workshops, furniture stores etc. Everywhere where high quality, design, space and lifting capacity are crucial aspects.

Fantastic loading opportunities are provided in every situation by the wide doors that come fully glazed as standard. As an alternative you can of course have the fire rated EI60 doors. All our push buttons are with both tactile and braille text.

Other possible options include: phones, different choices of flooring, locking, voice announcement, automatic door openers, level indicators, arrival bell, glazed shaft panels, lift painted in other RAL colors, elbow buttons, a mirror and more. See next page for examples.

A lift from Evolifts Limited is an investment for an easier and more comfortable everyday life, for a new standard of innovation and quality.



## Customization of Every Detail

At Evolifts we are proud of our ability to adapt our products to the preferences and wishes of our customers. Every lift that we make can be customized with a large range of options for you to choose from. Here is a small selection of the possibilities that we offer:



Hand rail in stainless steel



Key control



Level indicator



Automatic door opener



Telephone



Folding seat

# Specifications

<b>Recommended installation</b>	Indoors
<b>Rated load</b>	1000 kg
<b>Rated Speed</b>	max 0,15 m/sec
<b>Height limits</b>	max travel height 13m top Height 2,3 mm
<b>Pit depth</b>	110 mm
<b>Stops</b>	5 stops
<b>Standard platform sizes (w x d)</b>	1400 x 2000 / 1400 x 2500 / 1100 x 2200
<b>Standard lift dimensions (w x d)</b>	1830 x 2080 / 1830 x 2580 / 1530 x 2280 *, **
<b>Cut-out size</b>	+ 30 mm on above
<b>Other platform dimensions width</b>	1000 - 1400
<b>Lift dimension (w)</b>	+ 430 mm (+460 mm if door on B-side)
<b>Other platform dimensions depth</b>	1500 - 2500
<b>Lift dimension (d)</b>	+ 80 mm (if door on A & C +110mm)
<b>Cut-out size</b>	+ 30mm
<b>Standard Shaft finish</b>	Laminated sandwich panels in RAL 9003 (white) (T=25mm, H=565mm), Glazed panels optional.
<b>Standard platform finish</b>	RAL 9003 (white) All powder coated, other RAL colours available upon request, black rubber flooring.
<b>Doors</b>	Swing doors, doors can be on 3 sides
<b>Drive system</b>	Screw and nut
<b>Control system</b>	PLC
<b>Power supply</b>	380-400V 3-phase 50/60 Hz 16A, frequency converter
<b>Motor</b>	4 kW
<b>Battery emergency lowering</b>	incl. as standard
<b>Door buttons</b>	one touch
<b>Platform buttons</b>	Hold to run All buttons with tactile and braille
<b>Certification</b>	MD 2006 / 42 / EC
<b>Manufactured in</b>	Sweden

\* If door on side A & C=+30mm

\*\* If door on side B, w=+30mm